TOWN OF BELMONT

THE WINNING COMBINATION FOR

SEWER OVERFLOW MITIGATON WINN'S BROOK AREA

NEWEA Collection Systems Specialty Conference September 10, 2014






Winn's Brook Area


- Low-lying area in Northeast Belmont
- Close proximity to MWRA Flanders Road
- 85% of Belmont tributary to Flanders Road
- Extensive upstream sewer system
- Two different sewer subsystems











Reported Backups

Dates	Number	Rainfall (inches)
October 1996	29	10
June 1998	42	8
March 2001	32	7
May 2006	11	12

House Inspections

- 95 Houses have reported backups
- 69 Inspections conducted (73%)
- 49 Confirmed sewer overflows



Increased Hydraulic Grade Line Creates Sewer Overflows

- System Capacity Constraints
- Infiltration/Inflow in Belmont
 - 2007 Flow Monitoring Program
- Elevated downstream hydraulic grade line



Mitigation Concepts

- Increase sewer capacity
- Flow diversion
- Storage
- Isolation and Pumping
- I/I Removal



Solution Constraints

- No significant increase in flow to MWRA interceptor or transference of problem to Cambridge
- No transference of problem within Belmont
- Continued I/I reduction will be required
 - 2009 Sewer System Evaluation Survey



Alternative Combinations*

- 1. Increase gravity sewer capacity to pass 1-year storm
- 2. Divert upstream flow around WB (Brighton St.)
- 3. Divert, isolate with PS
- 4. Isolate with PS (no diversion)
- 5. Isolate with PS, extend FM to Flanders Rd.
- 6. Isolate with two pump stations
- *InfoWorks Sewer Model used to compare reduction in Winn's Brook HGL




Alternatives Combinations*

- 7. Two PS and line Channing & Brighton
- 8. Two PS, pump to 7.6 MG UST
- 9. Increase capacity to pass 06 Mother's Day
- 10. Divert, Two PS, pump to 3.3 MG UST
- 11. Divert, Two PS, pump to system

*InfoWorks Sewer Model used to compare reduction in Winn's Brook HGL





Cambridge Integration

- Cambridge not impacted
- Increased backwater condition
 - 3.6' increase
- Created transference within Belmont
 - Baker, Hittinger, Hamilton




Supplemental Alternatives

11A Divert (Dean St.), Two PS, pump to system

Divert with in-line storage (Dean St), Two PS, pump to system





Baseline Conditions

Alternative 12

Alternative 12A – 15% I/I Reduction

Predicted Discharge

	Peak Discharge MGD	24-Hour Volume MG
Baseline	16.53	15.34
Alternative 11	18.35 (+11.0%)	17.01 (+10.9%)
Alternative 12A	16.84 (+1.98%)	14.90 (-2.84%)

Construction Cost

(completed 12/11)

Winn's Brook Sewer Overflow Mitigation Facilities	\$4.9 Million
Townwide I/I Removal	\$1.1 Million
TOTAL	\$6.0 Million
























































Acknowledgements

Glenn Clancy, P.E., Town of Belmont
Director, Office of Community Development
Town Engineer

Peter Castanino, Town of Belmont

Director, Department of Public Works

Kurt Karlson, P.E., Fay, Spofford & Thorndike Lead Hydraulic Modeler



Questions?

Justin D. Gould, P.E., Fay, Spofford & Thorndike 781-221-1083 jgould@fstinc.com