

NEWEA 2016 Annual Conference Operator Ingenuity Session



Instruments and Methods used for Process Monitoring and Control of the North Attleborough, MA WWTF



January 26, 2016

Kaela Wiklund, North Attleborough WWTF Lab Supervisor

Dan Roop, Tighe & Bond

Outline



- Plant Overview
- Goals
- Instrumentation Introduction
- Equipment O&M
- Instrument Capabilities
- Final Thoughts



WWTF Overview



- **New 5-stage Bardenpho process**
- **New tertiary filtration system**
- **Upgrades to:**
 - Pump stations
 - Headworks building
 - First stage and RAS pumps
 - Odor control System
 - Plant water system
- **Treatment Goals**
 - Nitrogen removal
 - » Total nitrogen = 8 mg/L May-Oct
 - » Ammonia = 1 mg/L May-Oct
 - Phosphorus
 - » 0.1 mg/L Apr-Oct
 - » 1.0 mg/L Nov-Mar



WWTF Upgrade Commissioning – Process Monitoring Goals




- **Low level monitoring methods**
 - What is the best combination of approaches
 - » Field
 - » Insitu
 - » Colorimetric
- **Increased laboratory effort**
 - 2-person Staff
- **Instrumentation limits**
 - Reliability & Accuracy
 - Costs
- **What is best for Your Plant?**






Biological Nutrient Removal System - 5-Stage Bardenpho Process



Insitu Instrumentation



- **Ammonium Probes** - *Hach A-ISE NH4 Probe*
 - End of Aeration Zones
 - No longer in use
 - ISE Probes not accurate < 2 mg/L
 - Could use @ influent for ammonia loading
 - O&M
 - » Clean every 1-2 weeks
 - » Matrix correct 1-2 per month
 - » Replace cartridge 2x/year




Insitu Instrumentation



■ Nitrate Sensors - *Hach NITRATAX Plus sc NO3*

- Working well, reliable
- End of Anoxic Zones
 - » Mixed liquor recycle rate
 - » $< 1 \text{ mg/L}$ = increase NO_3 recycle
- End of Aeration Zones
 - » If $\text{NO}_3 < 8 \text{ mg/L}$, Eff TN good
 - » Eff TN reliably 2 mg/L less
- O&M
 - » Clean every 1 – 2 weeks
 - » Calibrate as required
 - » Replace wiper 2x/year
 - » Replace seals annually




How Are The Instruments Working?

Ammonium & Nitrate Insitu Probes Trending




- Calibration & confidence has taken time
- Recently interfaced SCADA & WIMS
- Continue to evaluate accuracy
- Rely on for trending

End of Aeration Insitu Ammonium Probe Hourly Trending



Insitu Nitrate Probes Hourly Trending



Insitu Instrumentation



- **pH Probes** - Hach Differential pH Sensor
 - End of Aeration
 - » Monitor nitrification drop levels
 - Tertiary Building
 - » Before chemical addition
 - O&M
 - » Clean every 1-2 weeks
 - » Calibrate every 60 days
 - » Replace salt bridge annually



Insitu Instrumentation



■ Dissolved Oxygen Probes - *Hach LDO*

- Aeration Tanks
- Trust for blower control
- Confirm accuracy daily
 - » Adjust offset if needed
- Clean weekly
- Replace end cap annually



Stock photo from www.Hach.com



Insitu Instrumentation



■ Turbidity Meter - Hach

SOLITAX Analyzer

- Tertiary Filter Effluent
- Show clarity
- Air entrapment issues from filter backwash
- Minimal maintenance



Equipment Maintenance




- Clean probes weekly
 - Cloth, brush and distilled water
- Calibration corrections as needed
- 2 person job
 - Lifting probes out of tanks



YSI ProPlus Quatro Handheld Probe – NH₄, NO₃, DO, Temperature



September 24 Train A & B Data



Laboratory Equipment and Testing – In-House



■ Testing for Process Monitoring / Control


- Spectrophotometer – Hach DR3900
 - » Ortho-P as P - *Ascorbic Acid Method* (#8048)
 - » Nitrate - *TNT 835 Low Range*
 - » Ammonia - *Salicylate Method* (#8155)

■ What's Important

- Reliability, time, cost
- Make immediate operational changes
- Anticipating 3rd party reportable test results




Laboratory Equipment and Testing- Monitoring Phosphorus Removal




Laboratory Equipment and Testing- In-house



- Microbiology for process monitoring
- Microorganisms are indicative of sludge health
- Interested in predominance of the following:
 - Rotifers
 - Stalked Ciliates
 - Free-Swimming Ciliates
 - Flagellates



Courtesy of CSU Sacramento, Operation of Wastewater Treatment Plants (Vol II, 6th ed.)



Lessons Learned & Recommendations



- **Every plant is different**
- **No substitute for an Operator's intuition**
- **Evaluate the appropriate level of instrumentation for each project**



Thank You



■ A Special Thanks to

- Merrill Hastings - North Attleborough WWTF Chief Operator
- Jack Horton – Retired North Attleborough WWTF Chief Operator
- Val Flaherty - North Attleborough WWTF Assistant Chief Operator
- Sue Mallon - North Attleborough WWTF Laboratory Technician
- Sue Guswa - Tighe & Bond



Associated Equipment Maintenance & Operational Costs



Do not show slide, keep for questions reference

	Test	Calibration & Maintenance	Required Costs	Other Comments
Nitrate	Handheld	~Calibrate daily	~Replace probe every 6 months ~ \$350 ± / probe	~ Aprox 20 - 30 min to calibrate and condition probe
	TNT	~Annual spec calibration ~No daily maintenance	~ \$38.50 / box of 25 vials ~ 6 tests / week = \$480 / year	~ Glass vials must be disposed of / recycled every test ~ Aprox 5 min / test
	Insitu	~Clean 1x / wk ~Replace profile & seals annually	~ Replace profile, seals, etc ~ Annual service contract ~ Consult Vendor for Price	~ Instant Readings ~ Viewable on SCADA ~ Recorded in WIMS
Ammonia / Ammonium	Handheld	~Calibrate daily	~Replace probe every 6 months ~ \$350 ± / probe	~ Aprox 20 - 30 min to calibrate and condition probe
	Pillow Packet	~Annual spec calibration ~No daily maintenance	~ \$112 / bags reagent for 100 tests ~ 8-10 tests / week = \$465 to \$582 / year	~ Corrosive final solution ~ Aprox 20 min / test once sample settled
	Insitu	~Clean 1x / wk ~Matrix correct 1x/ month ~Replace cartridge every 6 Months	~ Replace cartridge every 6 months ~ \$750 +/- consult vendor	~ Readings are instant ~ Viewable on SCADA ~ Recorded in WIMS
Phosphorous	Pillow Packet	~Annual spec calibration ~No daily maintenance	~ \$31.29 / bag, 100 tests ~ 15-20 tests / week = \$244 to \$325 / year	~ Aprox 5 min / test