



Massachusetts Water Resources Authority

# Wachusett Aqueduct Pumping Station Energy Optimization



**Stantec**

Thomas Renaud, PE, Massachusetts Water Resources Authority  
Michael Bartley, PE, Stantec



# Agenda

- Pumping Station Project Background
- Design and Construction
- Zero Net Energy Basics
- Zero Net Energy Project Improvements
- Onsite Energy Generation Measures
  - Photovoltaic System




- 
- Water System**
- Legend:**
- Blue: Water Bodies
  - Green: Forested Land
  - Yellow: Agricultural Land
  - White: Urban Land
  - Grey: Infrastructure
  - Red: Water Treatment Plant
  - Blue: Water Body
  - Green: Forested Land
  - Yellow: Agricultural Land
  - White: Urban Land
  - Grey: Infrastructure
  - Red: Water Treatment Plant
- Map Labels:** Quaker Reservoir, New Reservoir, Red Bank Reservoir, Delaware River, Eastern Harbor, Water Treatment Plant, etc.
- Scale:** 0 to 10 Miles
- North Arrow:** Indicated by an arrow pointing upwards.



# MWRA Water Redundancy Program

- Lack of tunnel redundancy from Wachusett Reservoir to John Carroll Water Treatment Plant (CWTP).







## Project Background

- **1898** – Wachusett Aqueduct was constructed.
  - 240 mgd capacity by gravity.





# Project Background


- **1966** – Cosgrove Tunnel replaced aqueduct as water supply source.
  - Wachusett Aqueduct maintained as emergency water supply source.
- **2003** – Wachusett Aqueduct rehabilitated and placed temporarily in service during construction of Cosgrove Tunnel connection to CWTP.



John J. Carroll Water Treatment Plant



# Wachusett Aqueduct Redundant Supply








# Pumping Station Design

- 122' x 68' and 51' high masonry building
  - 240 mgd design pump rate
  - 7 identical pumps (6 operating, 1 stand-by)
- Surge tank and storage yard



**BASEMENT PLAN**  
SCALE: 1/8" = 1'-0"





# Construction Schedule

- Construction Contract Award:  
November 18, 2015
  - Awarded at MWRA Board of Directors' Meeting to Barletta Companies (BHD/BEC Joint Venture 2015) for \$47,011,000.
- Construction Notice to Proceed: March 1, 2016
- Construction Substantial Completion: February 14, 2019





## Building Use

- Typically unoccupied.
- Used as necessary for emergencies.
- Pumps will be operated for a short period each month to ensure reliability.
- Annual operation of the entire station for testing & training.





# Why Look at Sustainable Design?

- Executive Order 484 – Leading by Example
  - Massachusetts LEED Plus
- Massachusetts Energy Code
- Zero Net Energy Goals





## What is Zero Net Energy?

*“A zero net energy building is one that is optimally efficient and, over the course of a year generates energy onsite, using clean renewable resources in a quantity equal to or greater than the total amount of energy consumed onsite.”*

*-Governor's Task Force*



## Optimally Efficient

- Building systems and envelope are as efficient as possible. Minimize energy consumption.
- Operations within the building are as efficient as practical without jeopardizing the effectiveness and readiness of the facility.



# Power Generation for Zero Net Energy

- Power that is generated onsite has to be from a renewable resource.
  - Solar, wind or hydroelectric systems
- Use of emergency generators is not considered a renewable resource.







# Zero Net Energy Process

1. Optimize Building Efficiencies
  - a) Kickoff Meeting: MWRA, Stantec and Architerra
  - b) Facility design and operating requirements reviewed
  - c) Workshop on preliminary ideas
  - d) Develop preliminary and final recommendations
2. Develop Energy Budgets for the Optimized Facility
  - a) Utilize Final Recommendations from Optimization
3. Develop Renewable Energy Source to account for Energy Budget



# Pumping Conditions Analyzed

- Standby Mode
  - Only building support systems; No Pumps
- Monthly Pump Operation
  - 1 hour each pump monthly
  - Includes Standby Mode loads
- Annual Operation Testing and Training
  - 3 days continuous pumping, maximum of 4 pumps
  - Includes Standby Mode + Monthly Pump Operation Loads





# Building Optimization

- Insulation Upgrades
  - Walls increased from R11.4 to R25.
  - Roof increased from R25 to R38.
  - Subgrade 2" slab on grade 4" on basement walls.
  - Continuous air barrier foundation to roof line.
  - Hard Ceiling in pump room.
- Lighting Optimization
  - High Efficiency Fixtures; Smart Controls.








## Cold Roof

- Continuous Air Gap
- Minimize heat gain in Summer
- Minimize heat loss in Winter
- Reduces ice dam potential





# Geothermal Heat Pump

- Geothermal Heating
  - Water cooled more efficient
  - Single piece of equipment for heating and cooling





# Geothermal Heat Pump

- Geothermal Heating
  - Uses source water for heating/cooling
  - Bypass allows free cooling







## Estimate of Energy Consumption

Operating Mode	Est. Annual Energy Use
Standby Mode	67,100 kWh
Standby and Monthly Maintenance	108,000 kWh
Standby Monthly Maintenance & Annual Training	216,600 kWh



# Solar System Design

- On-Site Energy Generation for Standby Mode Only
  - Power generation for monthly testing and annual training not feasible.
  - PV Cells on the roof and ground.
  - 84,000 kWh total; Some excess (+/- 16,900 kWh) provided.





# Revisions During Construction

- Construction Changes; Improvement in Solar Technology.
- Increased Efficiencies.
- Same relative footprint w/ more output.



- 90kW nominal DC;  
115,000 kWh production.
- Additional Pump Loads  
can be handled.





# Building Exterior, Surge Tank, and Solar Panels (May 2019)







# Final Conclusions

- Building Optimizations positive for any project.
- Large pumps used intermittently create unique energy totals.
- Design Conditions: Solar on site offsets building support Standby Mode.
- Construction Revisions: Additional Capacity could cover standby and monthly operation.





# Wachusett Aqueduct Pumping Station Energy Optimization

